

Dane techniczne

typ wentylatora: wentylator osiowy

Typ	prędkość obrotowa [obr./min]	moc silnika [kW]	wydajność max. [m³/h]	natężenie [A]	napięcie znam. [V]	poziom ciśnienia akustycznego* [dB(A)]	masa [kg]
AFC/2-250-025S	2850	0,25	2250	1,8	230V	72	15
AFC/2-315-037S	2860	0,37	3400	2,5	230V	74	17
AFC/2-355-055S	2860	0,55	4500	3,4	230V	77	30
AFC/2-250-025T	2760	0,25	2250	0,65	400V	72	15
AFC/2-250-037T	2800	0,37	2600	1	400V	72	15
AFC/2-315-037T	2800	0,37	3400	1	400V	74	17
AFC/2-315-075T	2800	0,75	5000	1,9	400V	77	20
AFC/2-355-055T	2790	0,55	4500	1,35	400V	77	30
AFC/2-355-110T	2780	1,1	5700	2,5	400V	78	35
AFC/2-400-150	2800	1,5	7800	3,4	400V	80	37
AFC/2-450-220	2800	2,2	9500	4,7	400V	81	57
AFC/2-450-300	2800	3	12000	6,5	400V	81	57
AFC/2-500-300	2800	3	15000	6,5	400V	81	60

* - w odległości 3 m

Dane techniczne

Typ	prędkość obrotowa [obr./min]	moc silnika [kW]	wydajność max. [m³/h]	natężenie [A]	napięcie znam. [V]	poziom ciśnienia akustycznego* [dB(A)]	masa [kg]
AFC/4-560-150	1440	1,5	14000	4,3	400V	82	65
AFC/4-630-220	1420	2,2	18200	4,8	400V	82	75
AFC/4-710-400	1440	4	25500	8,1	400V	83	80
AFC/4-800-400	1440	4	30000	8,1	400V	83	85
AFC/4-900-400	1440	4	32500	8,1	400V	83	90
AFC/4-900P-750	1440	7,5	43500	14,4	400V	83	108
AFC/4-1000-1100	1440	11	55000	21,2	400V	83	160
AFC/6-1250-1100	960	11	75000	22,2	400V	84	230
AFC/6-1500-1100	960	11	80000	22,2	400V	85	350
AFC/8-2000-1100	700	11	120000	25,1	400V	88	500

Wymiary [mm]

Typ	A	B	C	D	E	N*
AFC/2-250	310	280	300	250	8	8
AFC/2-315	375	345	330	315	8	8
AFC/2-355	426	395	380	355	10	8
AFC/2-400	500	450	380	400	10	8
AFC/2-450	550	500	430	450	10	8
AFC/2-500	600	550	450	500	12	12
AFC/4-560	660	610	450	560	12	12
AFC/4-630	736	690	500	630	12	12
AFC/4-710	810	760	470	710	12	12
AFC/4-800	900	850	480	800	12	12
AFC/4-900	1000	950	620	900	12	12
AFC/4-900P	1000	950	750	900	12	12
AFC/4-1000	1100	1050	730	1000	12	12
AFC/6-1250	1350	1310	800	1250	12	16
AFC/6-1500	1700	1600	800	1500	16	24
AFC/8-2000	2200	2100	1010	2000	18	24