

**KURKI KULOWE KOŁNIERZOWE DO PARY****PS 40 (DN 15 - DN 200)****PS 25 (DN 200 - DN 250)****PS 16 (DN 65 - DN 250)**

|                                                                                    |             |                        |
|------------------------------------------------------------------------------------|-------------|------------------------|
|  | <b>DN</b>   | <b>SYMBOL</b>          |
|                                                                                    | <b>15</b>   | <b>WKC 4a, 4d</b>      |
|                                                                                    | <b>20</b>   | <b>WKC 4a, 4d</b>      |
|                                                                                    | <b>25</b>   | <b>WKC 4a, 4d</b>      |
|                                                                                    | <b>32</b>   | <b>WKC 4a, 4d</b>      |
|                                                                                    | <b>40</b>   | <b>WKC 4a, 4d</b>      |
|                                                                                    | <b>50</b>   | <b>WKC 6a</b>          |
|                                                                                    | <b>65</b>   | <b>WKC 6a 16,40</b>    |
|                                                                                    | <b>80</b>   | <b>WKC 6a 40</b>       |
|                                                                                    | <b>100</b>  | <b>WKC 6a 16,40</b>    |
|                                                                                    | <b>125</b>  | <b>WKC 6a 16,40</b>    |
|                                                                                    | <b>150</b>  | <b>WKC 6a 16,40</b>    |
|                                                                                    | <b>200</b>  | <b>WKC 6a 40,25,16</b> |
|                                                                                    | <b>250*</b> | <b>WKC 6a 16, 25</b>   |

\* z przekładnią ręczną, PN 16 atm – 25 atm