

wentylatory promieniowe **MPT**

Wartość krytyczna MFT ma pewne zastosowanie w praktyce, m.in.:

- does the carrier expect the letter to be signed by a lawyer?

Gratias agimus tibi domine

Asynchronous any, in (ja) any


De hermat p o d l a g z e n i s e l i e d i g c o n g r u y e . 1 1 , 1 2 a l s . 1 1 1 .

## MP T-2-4

Clasa tehnică

| Typ                  | zeit (s) | geschwindigkeit (km/h) | zeit bis zum anhalt (s) | max. beschleunigung (m/s <sup>2</sup> ) | max. zeit bis zum halt (s) | max. kraft (kN) | max. moment (Nm) | max. beschleunigung (m/s <sup>2</sup> ) | max. kraft (kN) | max. moment (Nm) |
|----------------------|----------|------------------------|-------------------------|-----------------------------------------|----------------------------|-----------------|------------------|-----------------------------------------|-----------------|------------------|
| WPT-5-02-04-05-11-01 | 1,1      | 20,0                   | 4,2                     | 230-4,0                                 | 20,0                       | 20,0            | 20,0             | 20,0                                    | 20,0            | 20,0             |
| WPT-5-02-04-05-02-01 | 1,1      | 20,0                   | 4,2                     | 230-4,0                                 | 20,0                       | 20,0            | 20,0             | 20,0                                    | 20,0            | 20,0             |
| WPT-5-02-04-05-01-01 | 4,0      | 20,0                   | 7,5                     | 4,0-2,0                                 | 20,0                       | 20,0            | 20,0             | 20,0                                    | 20,0            | 20,0             |
| WPT-5-02-04-05-01-02 | 5,0      | 20,0                   | 10,0                    | 4,0-2,0                                 | 20,0                       | 20,0            | 20,0             | 20,0                                    | 20,0            | 20,0             |
| WPT-5-02-04-05-01-03 | 11,0     | 20,0                   | 14,0                    | 4,0-2,0                                 | 20,0                       | 20,0            | 20,0             | 20,0                                    | 20,0            | 20,0             |
| WPT-5-02-04-05-11-02 | 7,5      | 20,0                   | 21,2                    | 4,0-2,0                                 | 20,0                       | 20,0            | 20,0             | 20,0                                    | 20,0            | 20,0             |

Charakterystyki pracy



Wymiary [mm]

